

Soporte estampado de acero inoxidable AISI 304. Soporte giratorio de doble hilera de bolas.
Opcional freno total sobre soporte y rueda.

Nylon

Diámetro	Ancho	Carga Kgs.	Eje	Altura total	Plato mm.	Entre centros	Giratoria c/base	Giratoria c/base y freno	Fija
80	30	130	Liso	107	100x85	80x60	4232	4237	4242
100	30	150	Liso	128	100x85	80x60	4233	4238	4243
125	35	200	Liso	155	100x85	80x60	4234	4239	4244
160	40	250	Liso	197	140x110	105x80	4235	4240	4245
200	50	300	Liso	235	140x110	105x80	4236	4241	4246

4234



4239



4244



Diámetro	Ancho	Carga Kgs.	Eje	Altura total	Diámetro del Tornillo	Giratoria c/tornillo	Giratoria c/tornillo y freno
80	30	130	Liso	105	10/12	4134	4300
100	30	150	Liso	126	10/12	4161	4301
125	35	200	Liso	150	12	4299	4302

4299



4302



NYLON Y POLIURETANO

Diámetro	Ancho	Carga Kgs.	Eje	Altura total	Plato mm.	Entre centros	Giratoria c/base	Giratoria c/base y freno	Fija
80	30	100	Liso	107	100x85	80x60	3840	3845	3850
100	30	130	Liso	128	100x85	80x60	3841	3846	3851
125	35	200	Liso	155	100x85	80x60	3842	3847	3852
160	40	250	Liso	197	140x110	105x80	3843	3848	3853
200	50	300	Liso	235	140x110	105x80	3844	3849	3854

3843



3848



3853



Diámetro	Ancho	Carga Kgs.	Eje	Altura total	Diámetro del agujero	Giratoria c/agujero pasante	Giratoria c/agujero pasante y freno
80	30	100	Liso	105	10/12	3830	3833
100	30	130	Liso	126	10/12	3831	3834
125	35	200	Liso	150	12	3832	3835

3832



3835

